



DM



Water the Way You Like it!

Whether you like your Water Ice Cold or Steaming Hot, The Monet DM Delivers it Fresh and Clean!

Refill and Refresh

Elegant capacitive touch dispense icons, LCD smart alert display, and large 12-inch dispense area make refilling your favorite container quick and simple.

Designed with You in Mind

At Monet Water and Ice we believe that personal hydration products should reflect the people that use them, and the beauty, efficiency, and ease of use we all desire.

A Better Way to Hydrate

Monet's bottleless dispensers provide greater hygiene and increased sustainability compared to bottled options. The latest filtration and LED UV technologies provide a continuous supply of clean fresh tasting water without the need for bulky 5-gallon or plastic single-use bottles.

1318 Hart St., Honolulu, HI 96817

hawaiiwatertech.com


808-377-4311

 **HI WATER
TECHNOLOGY**



Effortless

Capacitive touch icons offer intuitive effortless dispensing.



Advanced

Internal microprocessor controls and monitors system functions.



Smart

LCD Smart screen displays messages, system status, and service alerts.



Accommodating

Extra-large 12-inch dispense area makes refilling even the largest containers a breeze.



Refreshing

Advanced reverse osmosis and multi-stage carbon filtration deliver a continuous supply of fresh, clean drinking water.



Clean

In-tank LED UV technology, anti-microbial surfaces, and no-touch filter changes keep the system clean inside and out.

DM 

Water the Way You Like it!

Ice Cold or Steaming Hot, The Monet DM Delivers it Fresh and Clean!



1318 Hart St., Honolulu, HI 96817

hawaiiwatertech.com

808-377-4311

 **HI** WATER
TECHNOLOGY

Monet Water DM Model Specifications



Model	DM-R
Power	
Voltage (V)	115Vac/60Hz
Power Consumption	400W
Cold Power Consumption	100W
Hot Power Consumption	300W
Hot Water System	
Temperature Control	Thermistor
Thermistor Cycle	1step : 158 - 165°F, 2step : 171 - 176°F, 3step : 178 - 183°F, 4step : 185 - 194°F
Hot Thermostat / Heat Limiter	Bi-metal (95°C +/- 1°C)
Hot Tank Size	0.79 gal (3 Liters)
Cold Water System	
Temperature Control	Thermistor
Thermistor Cycle	1step : 48 - 50°F, 2step : 46 - 47°F, 3step : 43 - 45°F, 4step : 39 - 42°F
Cold Tank Size	2.5 gal (9.4 Liters)
Feature	
Safety Hot	2 step Access
Key Access	Capacitive Touch Key
Display	LCD Module
Filter System	4 stage RO-80GPD (Optional pH/Mineral Filter Available)
In-Tank	UV LED
Color	Black
Weights and Measurements	
Net Weight	68 lbs. (31Kg)
Gross Weight	77 lbs. (35Kg)
Dimensions WxDxH	13.0" x 16.7" x 49.2" (330mm x 424.5mm x 1250mm)

DM  Cold & Hot Water

1318 Hart St., Honolulu, HI 96817

hawaiiwatertech.com

808-377-4311

 **WATER**
TECHNOLOGY